



'One Stop Centre' supplier for all scientific equipment, glassware and safety equipment for local and international industries

JATIKHAS SDN BHD (402338-A)

NO. 10 & 10-1, JALAN AVENUE 1 AMPANG AVENUE, 68000 AMPANG, SELANGOR

TEL: 03-4296 5355 FAX: 03-4295 6005

E-MAIL: sales@jatikhas.com WEBSITE: www.jatikhas.com

THERMOSTATIC WATER BATHS (STRETCHING INNER CHAMBER)



Features

- ◆ Stainless steel stretching inner container and roof cover.
- ◆ Intelligent temperature controller with PID program, digital tube display and function of timing and over-temperature protection.

Specifications

Model		BWB-2000-III(A)	BWB-2000-III(B)	BWB-2000-III(C)	BWB-2000-III(D)
		1 Hole	1 Row & 2 Holes	2 Rows & 4 Holes	2 Rows & 6 Holes
Heating Mode		Nature water convection heat transfer			
Function	Temp. Range	Ambient+5- 100°C			
	Temp. Resolution Ratio	0.1°C			
	Temp. Accuracy	±0.5°C			
	Temp. Uniformity	±1.0°C			
Structure	Inner Chamber	Stainless Steel			
	Outer Shell	Cold – rolled steel plate, resistance to chemical reagents coating on the surface			
	Heater	Stainless steel heating tube			
	Power Rating (kW)	0.4	0.5	1.0	1.5
Controller	Temp. Control Mode	PID			
	Temp. Setting Mode	Touch button setting			
	Temp. Display Mode	Measuring temperature displays on the three digital tubes upper row, set temperature displays on the lower row			
	Timer	0- 9999min (with timing wait function)			
	Operation Function	Fixed temperature operation, timing function, auto stop.			
	Program Mode	Optional			
	Additional Function	Deviation Correction, menu key locked, power failure back-up, power-off memory			
Safety Device		Over temperature alarm			
Specification	Inner Chamber size (W*L*H) (mm)	150*135*150	300*135*150	325*300*150	500*300*150
	Exterior Size (W*L*H) (mm)	170*154*210	318*2168*210	350*318*210	524*322*210
	Packing Size (W*L*H) (mm)	240*230*280	390*240*280	420*390*280	600*390*280
	Volume (L)	3.4	6.6	14.6	18.7
	Load per rack	5kg			
	Shelf Number	1			
	Power Supply (50/60Hz) Current rating	AC220V/1.8A	AC220V/2.3A	AC220V/4.5A	AC220V/6.8A
	NW/GW (kg)	3.3/4	4.5/5	6/7	7.5/9